



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**DOUBLE OPEN END SPANNER**  
**DOPPELMAUL-SCHLUSSEL**  
**CLES A FOURCHES**

**Manufactured to Din 3110 and IS : 2028 standards**

Professional Quality, drop forged from **Chrome Vanadium Steel** hardened, shank with heads set at 15".

**Finish :**

**CP(Chrome Plated Polished Head)**

**FCP(Fully Polished Chrome Plated)**

**SF(Satin Finish)**



Set no.	No. of pcs.	Contents	Weight(gms)
6m	6	6*7, 8*9, 10*11 12*13, 14*15, 16*17	401
8m	8	6*7, 8*9, 10*11 12*13, 14*15, 16*17, 18*19, 20*22	776
12m	12	6*7, 8*9, 10*11 12*13, 14*15, 16*17, 18*19, 20*22 22*23, 24*26, 25*27, 30*32	2223

Size	mm	6*7	8*9	8*10	10*11	12*13	12*14	13*14	13*16	13*17	14*15
Length	mm	120	140	140	155	170	188	170	188	205	188
Weight	gms	25	38	40	52	74	75	80	100	110	92

Size	mm	16*17	17*19	18*19	18*21	19*22	20*22	21*23	22*24	24*26	24*27
Length	mm	205	220	220	235	235	235	250	250	265	278
Weight	gms	120	160	170	205	205	205	250	250	330	360

Size	mm	25*27	25*28	27*30	27*32	30*32	30*36
Length	mm	278	278	300	300	300	328
Weight	gms	362	360	460	480	505	555

Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**DOUBLE OPEN END SPANNER**  
**DOPPELMAUL-SCHLUSSEL**  
**CLES A FOURCHES**

**Manufactured to IS : 2028 standards**

Professional Quality, drop forged from **Chrome Vanadium Steel** hardened, shank with heads set at 15".

**Finish :**

**CP(Chrome Plated Polished Head)**

**FCP(Fully Polished Chrome Plated)**

**SF(Satin Finish)**



Set no.	No of pcs.	Contents	Weight(gms)
5M	5	8*9,10*11,14*15,16*17,18*19	365
6M	6	6*7,8*9,10*11,12*13,14*15,16*17	303
66M	6	8*9,10*11,12*13,14*15,16*17,18*19	418
8M	8	6*7,8*9,10*11,12*13,14*15,16*17,18*19,20*22	613
12M	12	6*7,8*9,10*11,12*13,14*15,16*17,18*19,20*22,21*23,24*27,25*28,30*32	1693
5A	5	1/4*5/16,3/8*7/16,1/2*9/16,19/32*11/16,5/8*3/4	358
6A	6	1/4*5/16,3/8*7/16,1/2*9/16,19/32*11/16,5/8*3/4,13/16*7/8	533
6B	6	1/8*3/16,3/16*1/4,1/4*5/16,5/16*3/8,3/8*7/16,7/16*1/2	566
9B	9	1/8*3/16,3/16*1/4,1/4*5/16,5/16*3/8,3/8*7/16,7/16*1/2,1/2*9/16,9/16*5/8,5/8*3/4	1446

Size	mm	25*27	25*28	27*30	27*32	30*32	30*36
Length	mm	278	278	300	300	300	328
Weight	gms	362	360	460	480	505	555

Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**SINGLE OPEN END SPANNER**  
**EINMAUL-SCHLUSSEL**  
**CLES A FOURCHES**

**Manufactured to Din 894 and IS : 2028 standards**

Professional Quality German Type Engineer's Spanner with a raised collar around the open end and head set 15 degree., Drop forged from **Chrome Vanadium Steel** hardened, tempered and chrome plated or phosphated for corrosion protection.

**Finish :**

**Cs(Chrome Plated)**

**BF(Black Phosphated)**



Size	mm	7	8	9	10	11	12	13	14	15	16
Length	mm	77	93	100	106	111	124	138	138	157	157
Rate	gns	10	13	16	20	23	13	14	45	64	62

Size	mm	17	18	19	22	24	27	30	32	34	36
Length	mm	157	170	170	194	215	239	261	273	273	297
Rate	gns	60	78	75	110	150	180	260	320	300	450

Size	mm	38	41	46	50	55	60	65	70	75	80
Length	mm	297	377	377	410	456	527	527	575	575	690
Rate	gns	440	825	775	1050	1400	2050	2000	2850	2750	3800

Size	mm	85	90	95	100	105
Length	mm	690	690	725	750	800
Rate	gns	3650	3500	10150	10350	10850

Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- Spanner
- Plier
- Wrenches
- Socketry
- Tool Kit
- Hammers
- Screw Drivers
- Pullers
- Bolt Cutter
- Wheel Spanner
- Packaging

### DOUBLE OPEN END SPANNER

### DOPPELMAUL-SCHLUSSEL

### CLES A FOURCHES

### Manufactured to Din 895 and IS : 2028 standards

Professional Quality German Type Engineer's spanner with a raised collar around the open end and heads set at 15 degree. Drop forged from **chrome vanadium steel** hardened , tempered and chrome plated or phosphated for corrosion protection

#### Finish :

Cs(Chrome Plated)

BF(Black Phosphated)



Size	mm	6*7	8*9	8*10	9*10	9*11	10*11	10*12	10*13	11*12	13*14
length	ww	-	-	-	-	-	-	-	-	-	-
	mm	95	114	114	114	123	123	138	138	135	140
Weight	gms	15	20	24	24	37	37	40	40	46	48

Size	mm	11*13	12*13	12*14	13*15	13*16	13*17	14*15	14*17	16*17	17*19
length	ww	-	-	-	-	-	-	-	-	-	-
	mm	135	135	140	159	159	159	150	159	159	172
Weight	gms	43	45	55	75	75	75	80	75	75	100

Size	mm	18*19	17*22	18*21	19*22	20*22	22*27	19*24	22*24	24*27	27*30
length	ww	-	-	-	-	-	-	-	-	-	-
	mm	172	195	195	195	195	190	220	220	244	270
Weight	gms	123	140	140	140	140	180	174	200	250	375

Size	mm	27*32	30*32	30*34	30*36	32*36	36*41	41*46	46*50	50*55
	ww	-	-	-	-	3/4*7/8	7/8*1	1*1.1/8	1.1/8*1.1/4	-
	mm	270	270	270	303.5	303.5	342	370	402	450
Weight	gms	385	385	475	485	485	750	875	1270	1650

Size	mm	55*60	-
	ww	-	7/8*1.1/8
	mm	480	370
Weight	gms	1920	916

Copyright@2007-08. All rights reserved

[Privacy Policy](#)





- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**BIHEXAGON RING SPANNER  
DOPPELRING SCHLUSSEL**

**CLES POLYGAONALES :**

**Manufactured to DIN: 838 and IS 2029 Standards.**

Professional Quality thin walled chamfered rings ideal to reach recessed fasteners. **GRIPRITE** configuration drop forged from **chrome vanadium steel** hardened tempered and chrome plated for corrosion protection .

**Finish :**

**CS (chrome plated)**

**CP (chrome plated polished heads)**

**FCP (fully polished chrome plated)**

**SF (satin finish)**

Set no.	NQ DF Pcs	Contents	Weight(Gss)
8/6m	6	6x7,8x9,10x11,12x13,14x15,16x17	663
8/66m	6	8x9,10x11,12x13,14x15,16x17,18x19	984
8/8m	8	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22	1286
8/12m	12	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22,21x23,24x26,25x27,30x32	3357

Size	mm	6x7	8x9	8x10	10x11	12x13	12x14	13x14	13x16	13x17	14x15	16x17	14x17	16x18
	ww	-	-	-	-	-	-	-	-	-	1/4x5/16	-	-	-
Length	mm	161	173	173	196	219	219	222	232	245	232	245	245	245
Weight	gms	42	63	58	84	127	108	125	145	188	152	195	197	192

Size	mm	17x19	18x19	19x22	20x22	21x23	24x26	24x27	25x27	25x28	27x32	-	24x30	21x24
	ww	-	-	-	-	-	7/16x9/16	-	-	-	-	9/16x5/8	-	-
Length	mm	272	272	301	301	310	331	342	343	343	360	343	345	310
Weight	gms	248	273	335	350	378	495	498	530	490	650	504	544	390

Size	mm	22x24	27x30	30x32	30x36	32x36	36x41	41x46	46x50	55x60
	ww	-	-	-	-	3/4x7/8	7/8x1	1x1.1/8	1.1/8x1.1/4	-
Length	mm	312	364	364	400	400	441	483	533	160
Weight	gms	416	710	668	1000	900	1100	1550	1900	3550

Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- Spanner
- Plier
- Wrenches
- Socketry
- Tool Kit
- Hammers
- Screw Drivers
- Pullers
- Bolt Cutter
- Wheel Spanner
- Packaging

### BIHEXAGON RING SPANNER DOPPELRING-SCHLUSSEL

#### CLES POLYONALES:

Manufactured to **DIN: 897** and **IS : 2029** standards.

Professional Quality ring spanner with thin walled chamfered rings ideal to reach recessed fasteners. **GRIPRITE** configuration, Drop forged from **chrome vanadium steel** hardened, tempered and chrome plated for corrosion protection .

Finish :

CS(chrome Plated)

CP(Chrome Plated Polished Heads)



Set No	No. of,PCS	Content	Weight(gms)
5M	5	8x9,10x11,12x13,14x15,16x17	505
6M	6	6x7,8x9,10x11,12x13,14x15,16x17	537
8M	8	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22	1019
12	12	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22,21x23,24x27,25x28,30x32	2969
5A	5	3/8x7/16,1/2x9/16,5/8x11/16,3/4x25/32,13/16x7/8	890
6A	6	1/4x5/16,3/8x7/16,1/2x9/16,5/8x11/16,3/4x25/32,13/16x7/8	922

Size	mm	6x7	6x8	8x9	8x10	10x11	10x12	11x12	11x13	11x14	12x13	12x14	13x17	
	sae	-	1/4x5/16	5/16x3/8	-	3/8x7/16	-	-	-	-	-	7/16x1/2	-	-
	ww	-	-	-	-	1/8x3/16	-	-	-	-	3/16x1/4	-	-	
Length	mm	150	150	165	167	185	185	195	195	195	195	197	244	
weight	gms	32	32	47	47	73	68	90	90	90	90	92	155	

Size	mm	14x15	14x17	16x17	17x19	18x19	19x21	19x22	20x22	21x23	
	sae	1/2x9/16	-	5/8x11x16	11/16x3/4	-	3/4x25/32	3/4x7/8	13/16x7/8	-	-
	ww	1/4x5/16	-	5/16x3/8	19/32x11/16	5/8x3/4	3/4x13/16	-	7/16x1/2	-	-
Length	mm	219	244	246	254	255	274	275	275	301	
weight	gms	125	160	170	200	210	250	272	272	300	

Size	mm	22x24	-	24x26	24x27	25x28	27x32	30x32	-	-
	sae	7/8x15/16	-	5/16x1	-	1x1.1/8	-	-	1.1/16x1.1/8	1.1/16x1.1/4
	ww	-	7/16x9/16	-	1/2x9/16	9/16x5/8	-	5/8x3/4	-	-
Length	mm	304	312	323.5	324	349	368	372	368	368
weight	gms	345	370	425	420	580	622	650	642	594





- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**BIHEXAGON RING SPANNER  
DOPPELRING SCHLUSSEL**

**CLES POLYONALES :**

**Manufactured to DIN: 837 and IS 2029 Standards.**

Professional Quality thin walled chamfered rings .Drop forged from **Chrome Vanadium Steel** hardened,tempered and chrome plated for corrosion protection.

**Finish :**

**CS(Chrome Plated)**

**CP(Chrome Plated Polished Heads)**



Set No.	No of PCS	Content	Weight(gms)
4/6M	6	6x7,8x9,10x11,12x13,14x15,16x17	202
4/8M	8	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22	412
4/12M	12	6x7,8x9,10x11,12x13,14x15,16x17,18x19,20x22,21x23,24x27,25x28,30x32	1787

Size	mm	6x7	8x9	10x11	12x13	13x15	13x16	14x15	16x17	18x21	18x19
Length	mm	100	113	130	148	155	155	161	169	180	187
Weight	gms	10	17	25	40	60	60	45	65	100	90

Size	mm	20x22	21x23	22x24	24x27	25x28	30x32
Length	mm	210	235	235	262	290	320
Weight	gms	120	150	150	210	250	365

Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

### COMBINATION RING & OPEN END SPANNER

#### RING - MAULSCHUSSEL

#### CLES POLYGAONALES ET A FOURCHES

Manufactured to DIN :3113 and Is :6389 standards .

Professional Quality combination spanner with heads set at 15 degree for quick jobs, specially at narrow inconvenient places.

Drop forged from **chrome vanadium steel** hardened , tempered and chrome plated for corrosion protection .

#### Finish :

CS(Chrome Plated)

CP(Chrome Plated Polished Heads)



Set No.	No of PCS	Content	Weight
223/6m	6	8,10,12,13,14,17	339
223/8m	8	6,7,8,9,10,14,17,19	423
223/88m	8	8,9,10,11,13,14,17,19	479
223/12m	12	6,7,8,9,10,11,12,13,14,17,19,22	794
223/5a	5	3/8,7/16,1/2,9/16,5/8	276
223/6a	6	3/8,7/16,1/2,9/16,5/8,11/16	394

Size	mm	6	7	8	9	10	11	12	13	14	15	16
	sae	1/4	-	5/16	3/8	-	7/16	-	1/2	9/16	19/32	5/8
Length	mm	105	110	110	120	132	132	148	148	167	167	177
Weight	gms	15	20	20	25	35	35	50	56	70	70	90

Size	mm	17	18	19	20	21	22	23	24	25	26	27
	sae	11/16	-	3/4	-	13/16	7/8	-	15/16	1	-	1.1/16
Length	mm	188	208	208	230	230	250	250	275	278	280	307
Weight	gms	108	125	130	170	170	230	230	290	300	300	380

Size	mm	28	29	30	32
	sae	1.1/8	-	-	1.1/4
Length	mm	310	310	350	352
Weight	gms	380	400	550	550









- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**COMBINATION RING & OPEN END SPANNER  
RING - MAULSCHUSSEL  
CLES POLYGAONALES ET A FOURCHES  
Manufactured to DIN :3113 standards .**

Professional Quality combination spanner designed for easier handling. Drop forged from chrome **vanadium steel hardened**, tempered and chrome plated for corrosion protection. Equal openings at both ends. **GRIPRITE** pattern Bihexagon ring end offset at 15 degree and open end set at 15 degree .

**Finish :**

**CP(Chrome Plated Polished Heads)**

**FCP( Fully Polished Chrome Plated)**

**SF (Satin Finish )**



Set No.	No of PCS	Content	Weight (gms)
277/6M	6	8,10,12,13,14,17	454
277/8M	8	6,7,8,9,10,14,17,19	575
277/88M	8	8,9,10,11,13,14,17,19	654
277/12M	12	6,7,8,9,10,11,12,13,14,17,19,22	1027

Size	mm	6	7	8	9	10	11	12	13	14	15	16
	sae	1/4	-	5/16	-	3/8	7/16	-	1/2	9/16	19/32	5/8
Length	mm	150	125	130	135	140	150	160	170	190	205	250
Weight	gms	20	26	30	39	45	50	67	75	92	110	125

Size	mm	17	18	19	20	21	22	23	24	25	26	27
	sae	11/16	-	3/4	-	13/16	7/8	-	15/16	1	-	1.1/16
Length	mm	225	240	250	260	270	285	300	310	320	330	345
Weight	gms	145	162	178	197	210	260	280	312	375	383	430

Size	mm	28	30	32
	sae	1.1/8	-	1.1/4
Length	mm	360	375	390
Weight	gms	445	565	610



Copyright@2007-08. All rights reserved

[Privacy Policy](#)

- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**COMBINATION RING & OPEN END SPANNER**  
**RINGSEITE GEKROPFT - MAULSCHUSSEL**  
**CLES POLYGAONALES ET A FOURCHES:**  
**Manufactured to DIN :3113 standards .**

Professional Quality combination spanner designed for easier handling. Drop forged from chrome **vanadium steel hardened**, tempered and chrome plated for corrosion protection .Equal openings at both ends. **GRIPRITE** pattern bihexagon ring end offset at 15 degree and open end set at 15 degree .

**Finish :**  
**CP(Chrome Plated Polished Heads)**  
**FCP(Fully Polished Chrome Plated)**  
**SF (Satin Finish)**



Set No.	No of PCS	Content	Weight(gms)
278/6M	6	8, 10, 12, 13, 14, 17	506
278/8M	8	6, 7, 8, 9, 10, 14, 17, 19	629
278/88M	8	8, 9, 10, 11, 13, 14, 17, 19	730
278/12M	12	6, 7, 8, 9, 10, 11, 12, 13, 14, 17, 19, 22	1181

Size	mm	6	7	8	9	10	11	12	13	14	15
Length	mm	110	120	130	135	145	152	165	175	185	200
Weight	gms	22	28	35	41	52	62	74	89	99	120

Size	mm	16	17	18	19	20	21	22	23	24	25
Length	mm	210	225	240	250	260	275	285	305	315	325
Weight	gms	125	157	175	195	247	272	327	325	375	390

Size	mm	26	27	28	29	30	32
Length	mm	335	350	365	365	380	395
Weight	gms	480	520	555	540	635	690



Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**COMBINATION RING & OPEN END SPANNER**  
**RINGSEITE GEKROPFT - MAULSCHUSSEL**  
**CLES POLYGAONALES ET A FOURCHES:**  
**Manufactured to DIN :3113 standards .**

Professional Quality combination spanner designed for easier handling. Drop forged from chrome **vanadium steel hardened**, tempered and chrome plated for corrosion protection .Equal openings at both ends. **GRIPRITE** pattern bihexagon ring end offset at 15 degree and open end set at 15 degree .

**Finish :**  
**CP(Chrome Plated Polished Heads)**  
**FCP(Fully Polished Chrome Plated)**  
**SF (Satin Finish)**



Set No.	No of Pcs	Content	Weight (gms)
227/5M	5	8,10,12,14,17	336
227/6M	6	8,10,12,13,14,17	441
227/11M	11	6,7,8,9,10,11,12,13,14,17,19	751
227/14M	14	6,7,8,9,10,11,12,13,14,15,17,19,21,22	1376
227/5A	5	3/8,7/16,1/2,9/16,5/8	347
227/6A	6	3/8,7/16,1/2,9/16,5/8,11/16	497
227/9A	9	1/4,5/16,3/8,7/16,1/2,9/16,5/8,11/16,3/4	730
227/11A	11	1/4,5/16,3/8,7/16,1/2,9/16,5/8,11/16,3/4,13/16,7/8	1230
227/111A	11	3/8,7/16,1/2,9/16,5/8,11/16,3/4,13/16,7/8,15/16,1	1892
227/14A	14	3/8,7/16,1/2,9/16,5/8,11/16,3/4,13/16,7/8,15/16,1,1.1/16,1.1/8,1.1/4	3507
227/16A	16	1/4,5/16,3/8,7/16,1/2,9/16,5/8,11/16,3/4,13/16,7/8,15/16,1,1.1/16,1.1/8,1.1/4	3550

Size	mm	6	7	8	9	-	10	11	12	-	13	14	15
	sae	1/4	-	5/16	11/32	3/8	-	7/16	-	1/2	-	9/16	19/32
Length	mm	90	98	103.5	110	115	123	130	141	145	149	160	185
Weight	gms	18	23	25	32	35	41	47	60	65	75	90	110

Size	mm	16	17	18	19	20	-	21	22	23	24	25	27
	sae	5/8	11/16	-	3/4	-	13/16	-	7/8	-	15/16	1	1.1/16
Length	mm	185	210	210	235	260	260	271	285	310	310	325	360
Weight	gms	110	150	155	190	222	225	240	275	325	325	380	435

Size	mm	28	32	33	34	36	41	46	50
	sae	1.1/8	1.1/4	1.5/16	1.3/8	1.7/16	1.5/8	1.3/4	-
Length	mm	375	410	460	460	495	530	595	625



Weight	gms	550	630	1200	1200	1500	2000	2800	3015
--------	-----	-----	-----	------	------	------	------	------	------





- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**SINGLE OPEN END SLOGGING SPANNER**  
**EINMAUL SCHUSSEL IMPAKT**  
**CLES A FOURCHES IMPAKT**

**Manufactured to DIN: 133 and IS -4508 standards.**

Heavy duty impact spanner with strong profiled handle and durable striking end.  
 Drop forged from high grade **chrome vanadium steel** with head set at 15 degree .

**Finish :**  
**BF(black phosphated)**



Size	mm	30	32	36	41	46	50	55	60	65	70
Length	mm	200	200	210	225	280	280	320	320	342	370
Weight	gms	520	500	705	990	1800	1750	3025	2905	3850	4700

Size	mm	75	80	85	90	95	100	105	110	115	120
Length	mm	170	408	408	450	450	490	490	510	510	535
Weight	gms	4550	6850	6500	8880	8500	11500	11000	14600	17500	19000



Copyright@2007-08. All rights reserved

[Privacy Policy](#)



- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**SINGLE RING END SLOGGING SPANNER**

**EINMAUL SCHUSSEL IMPKT**

**CLES POLYGAONALES IMPAKT :**

**MANUFACTURED TO DIN 7444 AND IS : 4509 Standards.**

Drop forged from HIGH GRADE **Chrome Vanadium Steel** Heavy Duty Bihexagonalspanner with short, strong profiled handle with durable striking end and its 12 point opening allows it to be manipulated even in confined space.

**Finish :**

**BF(black phosphated)**



Size	mm	30	32	34	36	38	41	46	50	55	60
Length	mm	190	190	190	210	210	230	245	245	160	270
Weight	gms	480	465	410	550	575	750	870	1150	1400	1500

Size	mm	65	70	75	80	85	90	95	100	105	110
Length	mm	290	320	320	370	370	370	490	490	490	445
Weight	gms	1950	3800	3600	5500	5300	5100	8450	8150	7850	9300

Size	mm	115	120	130	135	145	150
Length	mm	445	450	515	515	570	570
Weight	gms	9000	10500	14000	13500	19500	19000









- **Spanner**
- **Plier**
- **Wrenches**
- **Socketry**
- **Tool Kit**
- **Hammers**
- **Screw Drivers**
- **Pullers**
- **Bolt Cutter**
- **Wheel Spanner**
- **Packaging**

**ADJUSTABLE SPANNER**  
**EINMA ULSCHLUSSEL VERSTELLBAR**  
**CLES A MOLETTE**

**Manufactured to DIN:3117 and IS: 6149 standards.**

Professional Quality drop forged from **chrome vanadium steel** with thin tapered jaws designed to get into narrow openings.

**Finish :**  
**CS(Chrome Plated)**  
**CP(Chrome Plated Polished Heads)**  
**BF(Black Phosphated)**



Stock no.	66-S-150	66-S-200	66-S-250	66-S-300	66-375
Length mm	150	200	250	300	375
Weight gms	130	240	375	610	1200

**PRO-SERIES**  
**Manufactured to DIN 3117 and IS: 6149 standards.**

Professional Quality drop forged from **chrome vanadium steel** with thin tapered jaws designed to get into narrow openings.  
 Moulded grip handle for comfortable working.

**Finish:**  
**CS(Chrome Plated)**  
**CP(Chrome Plated Polished Heads )**  
**BF(Black Phosphated)**



Stock no.	66-PS-200	66-PS-250	66-PS-300
Length mm	200	250	300
Weight gms	265	370	605





Copyright@2007-08. All rights reserved

[Privacy Policy](#)